

FUNCTION GENERATOR

Function Generator



GFG-8255A (5MHz)

- * Frequency Range: 0.5Hz ~ 5MHz
- * Waveforms: Sine, Triangle, Square, Ramp, TTL and CMOS Output
- * External Voltage Controlled Frequency (VCF) Function
- * Duty Cycle Control with Signal Inversion Capability
- * Variable DC Offset Control
- * Two-Step (-20dBx2) and Variable attenuator
- * Built-in 6 Digit Counter with INT/EXT Function up to 150MHz / high resolution
- * INT/EXT AM/FM Modulation * LIN/LOG Sweep Mode
- * GCV Output for Synchronization



GFG-8250A (5MHz)

- * Frequency Range: 0.5Hz ~ 5MHz
- * Waveforms: Sine, Triangle, Square, Ramp, TTL and CMOS Output
- * External Voltage Controlled Frequency (VCF) Function
- * Duty Cycle Control with Signal Inversion Capability
- * Variable DC Offset Control
- * Two-Step (-20dBx2) and Variable attenuator
- * Built-in 6 Digit Counter with INT/EXT Function up to 150MHz / high resolution

SPECIFICATIONS

MAIN	Frequency Range Amplitude Impedance Attenuator DC Offset Duty Control Display	0.5Hz ~ 5MHz (7 Range) > 10Vpp (into 50W load) 50W ±10% -20dB +1dBx2 <-5V ~ >5V (into 50W load) 80% : 20% : 80% to 1MHz Continue variable 6 digit LED display
SINE WAVE	Distortion Flatness	≤ 1%, 0.5Hz ~ 100kHz ≤ 0.3dB, below 500kHz ≤ 1dB, below 5MHz
TRIANGLE WAVE	Linear	≥ 98%, 0.5Hz ~ 100kHz ≥ 95%, 100kHz ~ 5MHz
SQUARE WAVE	Symmetry Rise or Fall Time	± 2%, 1Hz ~ 100kHz ≤ 50nS at maximum output (into 50W load)
CMOS OUTPUT	Level Rise or Fall Time	4Vpp ±1Vpp ~ 14.5Vpp ±0.5Vpp adjustable ≤ 120nS
TTL OUTPUT	Level Fan Out Rise or Fall Time	≥ 3Vpp 20 TTL load ≤ 25nS
VCF	Input Voltage Input Impedance	0V ~ 10V ±1V (100 : 1) 10kW ± 10%
GCV(FOR GFG-8255A ONLY)	Output Voltage	To set the voltage between 0V ~ 2V as per different frequency
SWEEP OPERATION (FOR GFG-8255A ONLY)	Sweep/Manual Sweep/Rate Sweep/Time Sweep/Mode	Switch selector 100 : 1 ratio max. and adjustable 0.5sec. ~ 30sec. adjustable Lin./Log. switch selector
AMPLITUDE MODULATION (FOR GFG-8255A ONLY)	Depth MOD. Frequency Carrier BW EXT Sensitivity	0 ~ 100% 400Hz (INT), DC ~ 1MHz(EXT.) 100Hz ~ 5MHz (-3dB) ≤ 10Vpp for 100% modulation
FREQUENCY MODULATION (FOR GFG-8255A ONLY)	Deviation MOD. Frequency EXT. Sensitivity	0 ~ ± 5% 400Hz (INT), DC ~ 20kHz(EXT.) ≤ 10Vpp for 10% modulation
FREQUENCY COUNTER	INT./EXT. Range Accuracy Time Base Resolution Input Impedance Sensitivity	Switch selector 0.5Hz ~ 5MHz (5Hz ~ 150MHz EXT.) Time base accuracy ± 1 count ± 20ppm (23°C ± 5°C) after 30 minutes warm up The maximum resolution is 100nHz for 1Hz and 1Hz for 100MHz 1MW// 150pF ≤ 35mVrms (5Hz ~ 100MHz) ; ≤ 45mVrms (100MHz ~ 150MHz)
POWER SOURCE		AC115V/230V ± 15%, 50/60Hz
ACCESSORIES		Power cord x 1, Instruction manual x 1, GTL-101 x 2
DIMENSIONS & WEIGHT		251(W) x 91(H) x 291(D)mm, Approx. 2.4kg

C4

ISO-9001 & ISO-14001